



**Please fill in on the PC & enclose with the consignment!**

Phone: +49 (0)821 450423-0  
E-Mail: registration@asg-analytik.de

To  
ASG Analytik-Service AG

Trentiner Ring 30  
D-86356 Neusäß

Sample description
urgency: <input type="checkbox"/> urgent (attention, 30% express surcharge) <input type="checkbox"/>

Parameter	required minimum sample quantity	Method	single measurements please mark
Density (15 °C)	50 ml	DIN EN ISO 12185	<input type="checkbox"/>
Calorific value, H <sub>o</sub>	10 ml	DIN 51900-1/-2	<input type="checkbox"/>
Flash point P.M.	150 ml	DIN EN ISO 2719	<input type="checkbox"/>
Kinetic viscosity (20 °C)	50 ml	DIN 51562-1	<input type="checkbox"/>
Distillation process	300 ml	DIN EN ISO 3405	<input type="checkbox"/>
Cloudpoint	100 ml	DIN EN 23015	<input type="checkbox"/>
CFPP	150 ml	DIN EN 116	<input type="checkbox"/>
Coke residue (from 10 % distillation residue)	200 ml	DIN EN ISO 10370	<input type="checkbox"/>
Sulfur content	10 ml	DIN EN ISO 20884 DIN EN ISO 20846 (alt.)	<input type="checkbox"/> <input type="checkbox"/> (alt.)
Water content	50 ml	DIN EN ISO 12937	<input type="checkbox"/>
Total pollution	600 ml	DIN EN 12662	<input type="checkbox"/>
Ash content	50 ml	DIN EN ISO 6245	<input type="checkbox"/>
Thermal stability (sediment)	300 ml	DIN 51371	<input type="checkbox"/>
<b>Complete DIN 51603-1</b>	1000 ml		<input type="checkbox"/>



additional parameters	required minimum sample quantity	Method	single measurements please mark
Red dye content	250 ml	DIN 51430	<input type="checkbox"/>
Solvent Yellow 124 content	250 ml	DIN 51430	<input type="checkbox"/>
Nitrogen content	10 ml	DIN 51444	<input type="checkbox"/>
Refractive index	20 ml	DIN 51423-2	<input type="checkbox"/>
C/H - ratio	10 ml	ASTM D 5291	<input type="checkbox"/>
Electrical conductivity	100 ml	DIN 51412-1	<input type="checkbox"/>
Element screening	20 ml	ASG 1912	<input type="checkbox"/>
GCxGC-TOF MS analytics	20 ml	ASG 2253	<input type="checkbox"/>
Peroxide number	50 ml	ASTM D 3703	<input type="checkbox"/>
Pourpoint	100 ml	DIN ISO 3016	<input type="checkbox"/>
Oxygen content	1 ml	DIN 51732 mod.	<input type="checkbox"/>
Heat capacity	150 ml	ASG 2023	<input type="checkbox"/>
Thermal conductivity	100 ml	ASTM D 2717	<input type="checkbox"/>
Ignition temperature	50 ml	DIN 51794	<input type="checkbox"/>

**Further desired test parameters and comments:**


**Address:**

Company	:	<input type="text"/>
Contact person	:	<input type="text"/>
Street	:	<input type="text"/>
ZIP, city	:	<input type="text"/>
Phone / Fax	:	<input type="text"/>
E-Mail	:	<input type="text"/>
VAT-ID	:	<input type="text"/> (for first order from EU countries)

Date

\_\_\_\_\_  
Signature